DEVBULK

DEVBULK DAMLA

Built Ship Yard :	July 2015
Flag:	MARSHALL ISLANDS
Class:	Rina & P&I Uk Club & ITF
Type:	BULK CARRIER (OPEN HATCH,SUPER BOX)
Dwat:	37,322 mts on 10,11 m Summer
Tpc:	46,5 mt on Summer Draft
L.o.a.:	177.85 m
Beam:	28,65 m
Moulded depth:	15,00 m

Tonnage:	(International):	gt/nt	**22,872 / 12,519**
	SUMMER	WINTER	TROPICAL
DEADWEIGHT	37.322 mts	36.290 mts	38.357 mts
DRAFT	10.957 m	10.731 m	11.183 m
FREEBOARD	4.043 m	4.269 m	3.817 m

Hatches: Hatch sizes:	No. 1	21.60 / 20.00 m Aft - 13.76 m Fwd
	No. 2	27.20 m x 24.00 m
	No. 3	27.20 m x 24.00 m
	No. 4	27.20 m x 24.00 m
	No. 5	28.00 m x 12.59 m Aft - 24.00m Fwd
Type of hatchcovers:	Hydraulic folding type	

Hold:	**Sizes:**	**Length**	**Grain / Bale (cub.m /f)**	**Grain / Bale**
	No 1:	21.60 m	6,466/ 6,390	229,558/ 226,874
	No 2:	27.20 m	10,028/ 9,902	355,995/ 351,534
	No 3:	27.20 m	10,051/ 9,950	356,844/ 353,239
	No 4:	27.20 m	10,009/ 9,908	355,324/ 351,731
	No 5:	28.00 m	8,996/ 8,906	319,366/ 316,18
Total capacity in cubic meters:			**45,550 / 45,056**	**1.617,087 / 1.599,559**

Hold:		**Tank Top m2**	**Permisseble Uniform Load**
	No 1:	22	. M/Ts
	No 2:	22	. M/Ts
	No 3:	22	. M/Ts
	No 4:	22	. M/Ts
	No 5:	22	. M/Ts

Gear:	4 cranes x 36 mts swl
Tanktop strength:	22 mts/sqm
Hatch Cover Strength:	No 1 : 5,0 mts/sqm & No 2,3,4,5 : 3,4 mts/sqm
Ventilation:	Electricity / Natural
Main Engine	Man - B&W 6S46ME // 7,050 Kw - 9585 Hp - 110,0 Rpm
Generators	Yanmar x 3 Set
Bunker Capacity	VLSIFO : 1194 m3 & LSMGO : 439 m3
Grabs	N/A
Speed/consumption:	
Loaded condition :	About 12,00 Knots on abt 18,00 mt VLSIFO + 0,1mt LSMGO
Ballast condition :	About 12,50 Knots on abt 18,00 mt VLSIFO + 0,1mt LSMGO
Port consumption :	About 3.0 mts VLSIFO
Winches working :	About 5.6 mts VLSIFO (Note: Local port regulations require the burning of LSMGO in port, e.g. EU ports)

All about, taken from plan but without guarantee.