

DEVBULK ASLAN

Built / Ship Yard:	Oshima Shipbuilding Co Ltd		
Flag:	Marshall Islands		
Class:	Rina		
P&I Club:	Uk Club		
Type:	Bulk Carrier / Open Hatch Super Box		
Dwt:	50,477 mts on 12,15 m Summer Draft		
Tpc:	53,86 mt on Summer Draft		
L.o.a.:	182,98 m		
Beam:	32,26 m		
Light Ship:	8878 mt		
Moulded Depth:	17,15 m		
Tonnage Gt / Nt	29,109/ 15,554		
	<u>Summer</u>	<u>Winter</u>	<u>Tropical</u>
Deadweight	50,477	49,116 mts	51,841 mts
Draft	12,15 m	11,89 m	12,68 m
Freeboard	5,03 m	5,30 m	4,52 m
Hatch Cover Size:	No		
	1	14,76 m x 19,80 m	
	2	20,50 m x 25,80 m	
	3	20,50 m x 25,80 m	
	4	20,50 m x 25,80 m	
	5	20,50 m x 25,80 m	
Hold Capacity:	No	Grain / Bale (Cub.m)	
	1	9,234 / 9,136	
	2	12,581 / 12,500	
	3	12,546 / 12,471	
	4	12,548 / 12,473	
	5	12,207 / 12,120	
	Total	59,117 / 58,700	
Type of Hatch Cover:	Hydraulic folding Type		
Gear:	4 Cranes x 30,0 mts Swl		
Grab:	N/A		
Ventilation/A60/CO2/ITF	Nat / Yes / Yes / Yes		
Tanktop Strength:	H1:47,2 , H2:47,2, H3:47,2, H4:47,2, H5:47,2 mts/sqm - 3x15mts & 2x 25 mts COIL		
Hatch Cover Strength:	H1:1,5, H2:1,5, H3:1,5, H4:1,5, H5:1,5 mts/sqm		
Main Engine:	MITSUI MAN B&W 6S50MC-C (MK 7)		
Generators:	6EY18ALx500KW x 900RPM x 3 Sets		
Bunker Capacity %85:	Vlsifo : Abt 1.400 m3 & Lsmgo : Abt 310 m3		
Speed/Consumption:			
Laden Condition:	Abt 12,00 Knots on abt 17,50 mt Vlsifo + 0,1 mt Lsmgo		
Ballast Condition:	Abt 12,50 Knots on abt 17,50 mt Vlsifo + 0,1 mt Lsmgo		
Port Consumption:	Abt 2,5 mt Vlsifo + 0,1 mt Lsmgo		
Winches Working:	Abt 5,6 mt Vlsifo + 0,1 mt Lsmgo		
	Note: Local port regulations require the burning of Lsmgo in port, e.g. EU ports		

ALL ABT.TAKEN PLAN BUT WITHOUT GUARANTEE